







Hoses with design factor 4:1  
**2380N**

## 2380N – High pressure hose



<b>CONSTRUCTION</b>	<b>Core tube</b>	: Polyamide
	<b>Pressure reinforcement</b>	: Two spiral layers and two open spiral layers of high tensile steel wire
	<b>Cover</b>	: Polyurethane, DN32: Polyamide
	<b>Standard colour</b>	: Black

**TEMPERATURE RANGE** -40°C up to +100°C

#														
	DN	size	mm	inch	mm	MPa	psi	MPa	psi	mm	kg/m			
<b>2380N-025V10</b>	4	-025	3.9	5/32	9.7	75.0	10,875	300	43,500	55	0.16			
<b>2380N-04V00</b>	6	-04	6.3	1/4	13.3	70.0	10,150	280	40,600	70	0.27			
<b>2380N-05V00</b>	8	-05	8.3	5/16	15.8	62.5	9,060	250	36,250	90	0.35			
<b>2380N-06V10</b>	10	-06	9.8	3/8	17.9	57.5	8,337	230	33,350	120	0.44			
<b>2380N-08V10</b>	12	-08	12.9	1/2	22.9	55.0	7,975	220	31,900	150	0.68			
<b>2380N-20V30</b>	32	-20	31.8	1 1/4	44.0	27.5	3,985	110	15,950	400	1.83			