



CA - DIN 20 078 N Light Series Metric
Swivel Female



XXXX-YY-ZZ Part Number	 Hose I.D.				 Metric thread	Tube O.D. mm	A mm	B mm	 W mm
	DN	inch	Size	mm					
1CA48- 6- 4	6	1/4	-4	6,3	M12x1,5	6	47	23	14
1CA48- 8- 4	6	1/4	-4	6,3	M14x1,5	8	46	22	17
1CA48-10- 4	6	1/4	-4	6,4	M16x1,5	10	46	22	19
1CA48-12- 4	6	1/4	-4	6,4	M18x1,5	12	46	22	22
1CA48- 8- 5	8	5/16	-5	7,9	M14x1,5	8	51	26	17
1CA48-10- 5	8	5/16	-5	7,9	M16x1,5	10	46	22	19
1CA48-12- 5	8	5/16	-5	7,9	M18x1,5	12	46	23	22
1CA48-10- 6	10	3/8	-6	9,5	M16x1,5	10	47	24	19
1CA48-12- 6	10	3/8	-6	9,5	M18x1,5	12	46	23	22
1CA48-12- 8	12	1/2	-8	12,7	M18x1,5	12	50	27	22
1CA48-15- 8	12	1/2	-8	12,7	M22x1,5	15	48	24	27
1CA48-18- 8	12	1/2	-8	12,7	M26x1,5	18	49	25	32
1CA48-15-10	16	5/8	-10	15,9	M22x1,5	15	54	29	27
1CA48-18-10	16	5/8	-10	15,9	M26x1,5	18	51	26	32
1CA48-18-12	20	3/4	-12	19,1	M26x1,5	18	51	25	32
1CA48-22-12	20	3/4	-12	19,1	M30x2	22	56	30	36
1CA48-28-16	25	1	-16	25,4	M36x2	28	63	33	41

Fittings with standard O-Ring seal can be used for temperatures from -30 °C up to +105 °C. Find O-Rings in section I. Special O-Ring on request.

Only items priced in current price list are carried in stock.
Material: zinc plated mild steel.
Dimensions shown may be changed at any time without prior notice.