



Pneumatic Valves Flexflow

ISO 5599-1, sizes 1 to 3

*Catalogue : PDE2596TCUK-ev
Edition : June 2007*



Solenoid coils with Din A or Industrial connection

Voltage	Order code Din A Standard 30 x 30	Weight (kg)	Order code Din A Mobile 30 x 30	Weight (kg)	Order code Industrial standard 22 x 30	Weight (kg)
Direct current						
12V DC	P2FCA445	0.105	P2FCA447	0.105	P2FCB445	0.093
24V DC	P2FCA449	0.105	P2FCA448	0.105	P2FCB449	0.093
48V DC	P2FCA453*	0.105	P2FCA474	0.105	P2FCB451	0.093
72V DC			P2FCA470	0.105		
96V DC			P2FCA471	0.105		
110V DC			P2FCA472	0.105		
Alternative current						
12V 50/60Hz	P2FCA440	0.105			P2FCB440	0.093
24V 50/60Hz	P2FCA442	0.105			P2FCB442	0.093
48V 50/60Hz	P2FCA469#	0.105				
110V 50Hz, 120V 60Hz	P2FCA453	0.105			P2FCB453	0.093
230V 50Hz, 230V 60Hz	P2FCA457	0.105			P2FCB457	0.093

* P2FCA453 is compatible with 110 V AC and 48 V DC

P2FCA469 is 24 V DC 6.8W or 48 V 50Hz 9.9 VA

Solenoid coils with M12 connection

Voltage	Order code 30 x 30	Weight (kg)	Order code 22 x 30	Weight (kg)
Direct current				
24V DC	P2FC6419	0.065	P2FC7419	0.065

Spare Solenoid Nuts

Valves requiring captured exhaust should be fitted with plastic knurled nut

Order code
P2FNP

Valves with vented exhaust are fitted with diffuser plastic nut

Order Code
P2FND

Spare Solenoid Operators

Solenoid pilot operator NC

Description	Order code No manual override	Weight (kg)	Order code Non-lock manual override	Weight (kg)	Order code Locking manual override	Weight (kg)
22 mm			P2FP13N4D		P2FP13N4C	
CNOMO	P2FP23N4A	0.065	P2FP23N4B	0.065	P2FP23N4C	0.065

Note.

Solenoid pilot operators are fitted to the Viking valve range. Order the above part numbers for spares. The operators are supplied with mounting screws and interface 'O' rings.

Coils and connectors must be ordered separately.

 Indicates stocked product.