

## Accessory Selection Guide – Spring Guard and Armor Guard

Parker Spring Guard and Armor Guard are two products that prolong the life of hose lines that are exposed to rugged operating conditions. They distribute bending radii to avoid kinking in hose lines and protect hose from abrasion and deep cuts. Guards are constructed of steel wire and plated to resist rust.



Spring Guard (SG)



Armor Guard (AG)

### Spring Guard/Armor Guard Application - Hose Type/Size

Spring Guard Part Number	Armor Guard Part Number	Inside Dia.	SS25UL 201, 206 221FR 225, 235 244 266	213 271 285 293	BXX 302 301LT 304 381 421WC	AX, MX 351TC, 351ST 422, 424 426, 431 436, 451TC 451ST, 471TC 471ST, 472TC 482TC, 482ST 273	601 604 636 646	701, 711 721, 721TC 721ST, 722LT 722TC, 772ST 774 787TC, 797TC	731, 781 782TC 782ST 791TC 792LT 792TC 831 836	801 804 821 821FR 831 881	811 811HT	275	761	Twin Line
SG-050	AG-050	0.50		-4		-3								
SG-060	AG-060	0.60	-4	-5	-3	-4		-3,-4			-4,-5			
SG-066	AG-066	0.66	-5	-6	-4	-5	-4							
SG-072	AG-072	0.72	-6		-5	-6		-5			-6			
SG-084	AG-084	0.84	-8	-8	-6	-8	-6	-6	-4,-6	-4	-8			
SG-097	AG-097	0.97	-10	-10	-8	-10	-8	-8	-8	-6	-10		-10	
SG-106	AG-106	1.06		-12	-10		-10			-8				
SG-113	AG-113	1.13	-12			-12		-10	-10		-12			
SG-122	AG-122	1.22			-12					-10			-12	-10
SG-131	AG-131	1.31	-16	-16				-12	-12	-12	-16	-12		
SG-155	AG-155	1.55	-20	-20	-16	-16		-16	-16		-16	-16	-16	-12
SG-161		1.61								-16				
SG-166		1.66											-20	
SG-182	AG-182	1.82	-24	-24		-20		-20	-20*		-20		-16	8-8
SG-209	AG-209	2.09			-20	-24			-20	-20			-24	
SG-232	AG-232	2.32	-32		-24					-24				-20
SG-292	AG-292	2.92									-40			

\*SG-182 for size -20 hose is only for 787TC and 797TC.

Note: Spring Guard and Armor Guard are packaged in 10 ft. pieces.

## Polyguard Strain Reliever

Temperature Range: -40°F to +225°F

Material: Flexible PVD

Color: Black (check for availability of other colors)

Part Number	Length inches	Hose O.D. inches
4PG	7	0.53
6PG	7	0.63
7PG	7	0.69
8PG	7	0.84

