


J7 Femelle tournant ORFS coude 45°


ISO 12151-1 – SWE 45°
SAE J516 – ORFS 45°



| XXXXX-XX-XX Référence 73 | D. Int. du tuyau | | | | Filetage UNF | A mm | B mm | E mm | W mm |
|--------------------------------|------------------|-------|--------|------|-----------------|---------|---------|---------|---------|
| | DN | pouce | module | mm | | | | | |
| 1J773-12-12-SM | 20 | 3/4 | -12 | 19,1 | 1-3/16x12 | 105 | 57 | 21 | 36 |
| 1J773-16-12-SM | 20 | 3/4 | -12 | 19,1 | 1-7/16x12 | 107 | 59 | 24 | 41 |
| 1J773-16-16-SM | 25 | 1 | -16 | 25,4 | 1-7/16x12 | 119 | 69 | 24 | 41 |
| 1J773-20-16-SM | 25 | 1 | -16 | 25,4 | 1-11/16x12 | 131 | 80 | 26 | 50 |
| 1J773-20-20-SM | 32 | 1-1/4 | -20 | 31,8 | 1-11/16x12 | 154 | 90 | 30 | 50 |

J9 Femelle tournant ORFS coude 90°

ISO 12151-1 – SWES
SAE J516 – ORFS 90°



| XXXXX-XX-XX Référence 73 | D. Int. du tuyau | | | | Filetage UNF | A mm | B mm | E mm | W mm |
|--------------------------------|------------------|-------|--------|------|-----------------|---------|---------|---------|---------|
| | DN | pouce | module | mm | | | | | |
| 1J973-12-12-SM | 20 | 3/4 | -12 | 19,1 | 1-3/16x12 | 101 | 53 | 48 | 36 |
| 1J973-16-12-SM | 20 | 3/4 | -12 | 19,1 | 1-7/16x12 | 114 | 66 | 56 | 41 |
| 1J973-16-16-SM | 25 | 1 | -16 | 25,4 | 1-7/16x12 | 120 | 70 | 56 | 41 |
| 1J973-20-16-SM | 25 | 1 | -16 | 25,4 | 1-11/16x12 | 127 | 77 | 64 | 50 |
| 1J973-20-20-SM | 32 | 1-1/4 | -20 | 31,8 | 1-11/16x12 | 151 | 87 | 69 | 50 |

Série d'embouts compatible avec les tuyaux:

SM: 6 pans métrique

73 731