



# Coupleur hexagonal femelle FHC



Référence Parker	Filetage femelle NPT		L HEX	D (po.)	Pression de service (PSIG)		
	T <sub>1</sub>	T <sub>2</sub>			Laiton	Acier inoxydable	Acier
1-1 FHC	1/16	1/16	1/2	0,75	4 500	7 500	8 000
2-1 FHC	1/8	1/16	5/8	0,75	4 000	6 400	6 800
2-2 FHC	1/8	1/8	5/8	0,75	4 000	6 400	6 800
4-1 FHC	1/4	1/16	3/4	0,92	4 300	6 600	7 000
4-2 FHC	1/4	1/8	3/4	0,94	4 300	6 600	7 000
4-4 FHC	1/4	1/4	3/4	1,13	4 300	6 600	7 000
6-1 FHC	3/8	1/16	7/8	0,95	3 500	5 300	5 600
6-2 FHC	3/8	1/8	7/8	1,03	3 500	5 300	5 600
6-4 FHC	3/8	1/4	7/8	1,13	3 500	5 300	5 600
6-6 FHC	3/8	3/8	7/8	1,13	3 500	5 300	5 600
8-2 FHC	1/2	1/8	1-1/8	1,22	3 600	5 200	5 500
8-4 FHC	1/2	1/4	1-1/8	1,38	3 600	5 200	5 500
8-6 FHC	1/2	3/8	1-1/8	1,50	3 600	5 200	5 500
8-8 FHC	1/2	1/2	1-1/8	1,50	3 600	5 200	5 500
12-2 FHC	3/4	1/8	1-3/8	1,39	3 000	4 300	4 600
12-4 FHC	3/4	1/4	1-3/8	1,55	3 000	4 300	4 600
12-6 FHC	3/4	3/8	1-3/8	1,69	3 000	4 300	4 600
12-8 FHC	3/4	1/2	1-3/8	1,88	3 000	4 300	4 600
12-12 FHC	3/4	3/4	1-3/8	1,53	3 000	4 300	4 600
16-2 FHC	1	1/8	1-5/8	1,44	3 100	4 500	4 800
16-4 FHC	1	1/4	1-5/8	1,63	3 100	4 500	4 800
16-6 FHC	1	3/8	1-5/8	1,63	3 100	4 500	4 800
16-8 FHC	1	1/2	1-5/8	1,77	3 100	4 500	4 800
16-12 FHC	1	3/4	1-5/8	1,72	3 100	4 500	4 800
16-16 FHC	1	1	1-5/8	1,89	3 100	4 500	4 800
20-16 FHC	1-1/4	1	2	1,94	2 300	3 500	3 700
20-20 FHC	1-1/4	1-1/4	2	1,94	2 300	3 500	3 700
24-24 FHC	1-1/2	1-1/2	2-3/8	1,94	2 100	3 200	3 400