






192YX – Femelle tournant BSP 60°



MATÉRIAUX Acier galvanisé, passivé transparent sans Cr(VI).
Autres matériaux disponibles sur demande.

| Référence # | DN Mod mm Pouce | | | | Type de raccordement Filetage | A mm | B mm | J mm | Max. WP MPa |
|--------------------|---|-----|------|------|---|---------|---------|---|---|
| |  | | | |  | | |  |  |
| 192YX-4-03 | 5 | -03 | 4.8 | 3/16 | G 1/4 | 42 | 16 | 17 | 63.0 |
| 192YX-4-04 | 6 | -04 | 6.3 | 1/4 | G 1/4 | 44 | 17 | 17 | 63.0 |
| 192YX-6-05 | 8 | -05 | 7.9 | 3/16 | G 3/8 | 45 | 17 | 19 | 55.0 |
| 192YX-6-06 | 10 | -06 | 9.5 | 3/8 | G 3/8 | 46 | 19 | 22 | 55.0 |
| 192YX-8-06 | 10 | -06 | 9.5 | 3/8 | G 1/2 | 46 | 19 | 27 | 43.0 |
| 192YX-8-08 | 12 | -08 | 12.7 | 1/2 | G 1/2 | 52 | 21 | 27 | 43.0 |
| 192YX-12-10 | 16 | -10 | 15.9 | 5/8 | G 3/4 | 50 | 19 | 32 | 35.0 |
| 192YX-12-12 | 20 | -12 | 19.0 | 3/4 | G 3/4 | 56 | 21 | 32 | 35.0 |
| 192YX-16-12 | 20 | -12 | 19.0 | 3/4 | G 1 | 56 | 22 | 41 | 28.0 |
| 192YX-16-16 | 25 | -16 | 25.4 | 1 | G 1 | 57 | 22 | 41 | 28.0 |
| 192YX-20-16 | 25 | -16 | 25.4 | 1 | G 1 1/4 | 58 | 24 | 50 | 25.0 |