


Raccords d'implantation

3198

Té au centre, mâle BSP et métrique



Polymère technique, laiton nickelé,
NBR



ØD	C		E	F	G	H	L/2	kg
4	M5x0,8	3198 04 19	3,5	8	8,5	17,5	14	0,003
	G1/8	3198 04 10	5	13	8,5	15	14	0,006
	G1/4	3198 04 13	5,5	16	8,5	15	14	0,011
6	M5x0,8	3198 06 19	3,5	8	10,5	19,5	16	0,004
	G1/8	3198 06 10	5	13	10,5	17	16	0,007
	G1/4	3198 06 13	5,5	16	10,5	17	16	0,012
8	G1/8	3198 08 10	4,5	13	13,5	23,5	23	0,011
	G1/4	3198 08 13	5,5	16	13,5	21,5	23	0,014
	G3/8	3198 08 17	5,5	20	13,5	21,5	23	0,019
10	G1/4	3198 10 13	5,5	16	16	26	26,5	0,017
	G3/8	3198 10 17	5,5	20	16	24	26,5	0,020
	G1/2	3198 10 21	7,5	24	16	24	26,5	0,029
12	G1/4	3198 12 13	5,5	16	19	29	31	0,021
	G3/8	3198 12 17	5,5	20	19	27	31	0,024
	G1/2	3198 12 21	7	24	19	27	31	0,033
14	G3/8	3198 14 17	5,5	20	22	32,5	35,5	0,036
	G1/2	3198 14 21	7	24	22	27	35,5	0,036
16	G3/8	3198 16 17	7,5	27	27	54,5	38,5	0,121
	G1/2	3198 16 21	9	27	27	54,5	38,5	0,117

Raccord orientable